


# Elcometer 7400 Compact Moisture Meter



Elcometer 7400 Compact Moisture Meter

**At a glance**

- Compact, easy to use gauge.
- Can be used to measure moisture content of sawn timber, chipboard & fibreboard.
- Measure moisture content in substrates up to 25mm thick.

**Elcometer 7400 Compact Moisture Meter**

The hand closes naturally around the ergonomic form of the housing so that the pins on the end of the instrument can be pressed into the material to be measured. The thin pins make it easy to measure the moisture content of sawn timber, chipboard and fibreboard materials up to a maximum thickness of 25 mm as well as normal gypsum or mixed plaster.

- Handy, quick pocket-sized moisture meter for speedy single or series measurements.
- Two-group wood species correction.
- Measurement of plaster moisture content with a direct readout in percentage of dry weight.
- Completely automatic instrument setting.
- No separate electrodes or leads required.

**Moisture**

One of the most regular causes of a coating’s failure is moisture. It is not sufficient to simply ensure that the surface is dry as often the surface of the substrate is the driest point – due to evaporation.

Many substrates in industry today that are coated are porous and can absorb moisture. It is necessary to measure the moisture content within the substrate to reduce the possibility of subsequent coating failure.

When powder coating substrates which have a high moisture content, - such as wood or MDF, steam will generate during the curing process damaging the new coating. Other substrates, which may have a high moisture content, include concrete, fibreboard, plasterboard, gypsum and brick.

<b>Measuring Range</b>	5 to 20% moisture content for wood with two-group species correction 0.3 to 3.5% moisture content for plaster, with large 3-digit LCD readout.
<b>Dimensions</b>	200mm x 35mm x 35mm (7.87" x 1.38" x 1.38")
<b>Weight</b>	130g (4.6oz)
<b>Power supply</b>	9 V dry cell or rechargeable battery
<b>Part Number</b>	K0007400M018

## Related products



Elcometer 7400  
Compact A



Elcometer 7400  
Compact B

The measuring principle of the COMPACT "A" is based on the dielectric constant or high frequency method. The meter is simply placed on the material to be tested, the moisture content can be read off immediately. No need to drive pins into the wood.

Electronic structural moisture indicator using a patented technique based on the dielectric constant/ high frequency method. The indicator is equipped with a digital LCD readout and a universally applicable ball sensor for non-destructive location of moisture concentration in all kinds of building materials as well as for assessment of moisture distribution in walls, floors and ceilings.

### ENGLAND

Elcometer Ltd  
Edge Lane  
Manchester M43 6BU

Tel: +44 (0)161 371 6000  
Fax: +44 (0)161 371 6010  
e-mail: [sales@elcometer.com](mailto:sales@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

### USA

Elcometer Inc  
1893 Rochester Industrial Drive  
Rochester Hills Michigan 48309

Tel: +1 248 650 0500  
Toll Free: 800 521 0635  
Fax: +1 248 650 0501  
e-mail: [inc@elcometer.com](mailto:inc@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

### CANADA

Elcometer Ltd  
PO Box 622, 401 Ouelette Avenue  
Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500  
Toll Free: 800 521 0635  
Fax: +1 248 650 0501  
e-mail: [ca\\_info@elcometer.com](mailto:ca_info@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

### ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd  
896 Dunearn Rd  
Sime Darby Centre #3-09  
Singapore 589472,  
Republic of Singapore

Tel: +65 6462 2822  
Fax: +65 6462 2860  
e-mail: [asia@elcometer.com](mailto:asia@elcometer.com)  
[www.elcometer.com](http://www.elcometer.com)

### BELGIUM

Elcometer SA  
Rue Vallée 13  
B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10  
Fax: +32 (0)4 374 06 03  
e-mail: [be\\_info@elcometer.be](mailto:be_info@elcometer.be)  
[www.elcometer.be](http://www.elcometer.be)

### FRANCE

Elcometer Sarl  
97 Route de Chécý  
45430 BOU

Tel: +33 (0)2 38 86 33 44  
Fax: +33 (0)2 38 91 37 66  
e-mail: [fr\\_info@elcometer.fr](mailto:fr_info@elcometer.fr)  
[www.elcometer.fr](http://www.elcometer.fr)

### GERMANY

Elcometer Instruments GmbH  
Ulmer Strasse 68  
D-73431 Aalen

Tel: +49 (0)7361 52806 0  
Fax: +49 (0)7361 52806 77  
e-mail: [de\\_info@elcometer.de](mailto:de_info@elcometer.de)  
[www.elcometer.de](http://www.elcometer.de)